



## VERIFICATION OF COMPLIANCE

No.: **GZES2211022307PV01**

Applicant: **Huawei Solar Limited**  
No. 5, 17F, Strand 50, Bonham Strand, Sheung Wan, Hong Kong

Manufacturer: **Huawei Solar Limited**  
No. 5, 17F, Strand 50, Bonham Strand, Sheung Wan, Hong Kong

Product Name: Hybrid Inverter

Product Description: Three Phase Hybrid Inverter

Model No.: FU-SUN-29.9K-SG01HP3-EU-BM3, FU-SUN-30K-SG01HP3-EU-BM3  
FU-SUN-35K-SG01HP3-EU-BM3, FU-SUN-40K-SG01HP3-EU-BM4  
FU-SUN-50K-SG01HP3-EU-BM4

Trade Mark: **FUJI** SOLAR

Rating: Refer to page 2

Intended Use: PV System

Protection against Electric Shock: Class I

Additional Information (if any): IP 65

Software version: MAIN: Ver 3102

Sufficient samples of the product have been tested and found to be in conformity with

Test Standard: Refer to page 2

as shown in the

Test Report Number(s): GZES221102230701, GZES221102230702

This Verification of Compliance has been granted to the applicant based on the results of tests, performed by Laboratory of SGS-CSTC Standards Technical Services Co., Ltd. on sample of the above-mentioned product in accordance with the provisions of the relevant specific standards.

David Guo

Senior Technical Manager  
SGS-CSTC

2023-03-03

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services which can be accessible at <https://www.sgs.com/en/terms-and-conditions>  
Member of SGS Group (Société Générale de Surveillance)

No.:

GZES2211022307PV01

Other information added :  
Ratings

Model	FU-SUN-29.9K-SG01HP3-E U-BM3	FU-SUN-30K-SG01HP3-E U-BM3	FU-SUN-35K-SG01HP3-EU-BM3	FU-SUN-40K-SG01HP3-EU-BM4	FU-SUN-50K-SG01HP3-EU-BM4
PV Input					
Recommended Max. PV input power	38870 Wp	39000 Wp	45500 Wp	52000 Wp	65000 Wp
Max. input voltage	1000 V				
Start-up operating voltage	180 V				
Rated input voltage	600 V				
MPPT operating voltage range	150~850 V				
Full power MPPT voltage range	360~850 V	360~850 V	420~850 V	360~850 V	450~850 V
Max. input current	36/36/36 A			36/36/36/36 A	
Max. short current	55/55/55 A			55/55/55/55 A	
Battery Input					
Battery Type	Li-Ion				
Battery Voltage Range	160~800 V				
Max. Charging Current	50/50 A				
Max. Discharging Current	50/50 A				
AC Output					
Nominal grid voltage	3/N/PE, 230/400 Vac				
Nominal grid frequency	50/60 Hz				
Rated AC power	29900 W	30000 W	35000 W	40000 W	50000 W
Max. AC power	29900 VA	33000 VA	38500 VA	44000 VA	55000 VA
Rated AC current	43.4 A	43.5 A	53.1 A	60.7 A	75.8 A
Max. AC current	43.4 A	47.9 A	55.8 A	63.8 A	79.8 A
Output power factor	1 default (adjustable+/-0.8)				
General Data					
Operating temperature range	-40 °C ~ +60 °C (Above 45 °C Derating)				
Protection degree	IP65				
Protective class	Class I				
Cooling method	Smart cooling				
Topology	Transformerless				

Test

Standards:

IEC 62116:2014. Test procedure of islanding prevention measures for utility-interconnected photovoltaic inverters.

IEC 61727:2004. Photovoltaics (PV) systems - Characteristics of the utility interface.



David Guo

Senior Technical Manager  
SGS-CSTC



2023-03-03

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services which can be accessible at <https://www.sgs.com/en/terms-and-conditions>

Member of SGS Group (Société Générale de Surveillance)